

## **Print Serial# BarCode Labels**

**PROGRAM NAME:** BARSER

**MENU OPTION TITLE:** Print Serial# Barcode Labels

**MAIN MODULE:** BAR CODE SYSTEM

**HELP KEY ACTIVE:** No

### **PROGRAM OVERVIEW**

This program will print one barcode label for all the serial numbers received on the date you select. It is specifically written for a "BARCODE BLAZER" brand printer and prints barcode style "Barcode E/Code 128", on a 3" wide by 1" tall label. It will print the UPC barcode for the serial number, the actual serial number underneath the barcode, and the word "SERIAL#" on the label. (NOTE: this print can be changed according to customer)

This program generates a text file on your hard drive with the proper language in it to print the barcode label. This file will be stored in the first path you have configured on your computer. Make sure that this path runs to the directory that includes the Dataflex program "DFRUN". This way, the program can find the file and send it to the proper port. The default port name is COM2.

Next, if you are printing to a serial or com port instead of a parallel or LPT port, you will need to execute an "MSDOS" command either during your boot up of the PC or in the "SETPATH" file of your shortcut that runs the IBS software. This command is necessary to match up the speed of the serial/com port with the serial printer. This command is as follows: "MODE COM2:96,N,8,1". The code may be different that this, according to how the PC is set up and the printer serial port as well. If you have trouble with this you will need to contact your IBS representative or an experienced PC technician.

### **PROGRAM OPERATION**

**ENTER RECEIVED DATE:** This is the date the serial number was received into the system.

**ENTER GUNTYPE:** This is the guntype or "fedbook" that you wish to print from.

**ENTER RECEIVING NAME:** This is not important.

**BEGINNING SERIAL#:** This is not active.

**ENDING SERIAL#:** This is not active.

**Is this information correct (Y/N)?**